

Opening Name/ Number:			
W.I.C.	H.I.C.	Wall Type/ Thickness	Swing

Frame Details

Frame Type:
16-GA. SS 304-4 Brushed One Part Frame: ____(Optional) Foamed Standard Frame: ____
16-GA. SS 304-4 Brushed Two-Part Frame ____ 4" Molded Fiberglass Frame: ____

Hinges:
3 SS Standard Weight 4½" x 4½" Hinges: ____

Gaskets:
Door Silencers: ____ Self Adhesive Silicone Smoke/Weatherseal: ____
Pro Series SS Adjustable Jamb Mounted Gasket: ____
CS Series Aluminum Adjustable Jamb Mounted Gasket:____

Door Details

Door Panel:
1-3/4" Molded Fiberglass Door: ____

Closer:
Pro Series Closer with SS Painted Arm: ____ SS Cover Upgrade: ____
CS Series Closer with Aluminum Painted Steel Arm: ____

Vision Panel:
SS Vision Panel:
5" x 28": ____ 22" x 28": ____
¼" Abraision Resistant Polycarbonate: ____
1" Clear Tempered Argon Insulated Glass: ____
Safety Film: Yes / No One Side: ____ Both Sides: ____
Fiberglass Flush 20" x 30" x ⅜" Abraision Resistant Polycarbonate Vision Panel: ____

Exit/Entry:
SS Rounded Push/Pull Set: ____
CS Series CYLINDRICAL LEVER: Passage Lever: ____ Lever Lockset: _____
Pro Series SS MORTISE LEVER: Passage Lever: ____ Lever Lockset: _____
Pro Series SS Rim PANIC BAR: Exit Only: ___ Passage Trim: ___ Lever Lockset: _____
CS Series Painted Rim PANIC BAR: Exit Only: ___ Passage Trim: ___ Lockset Trim:_____
Controlled Access Hardware Needed: _____

Kick Plate: SS 304-4 Brushed
8" Tall: ____ 12" Tall: ____ 28" Tall :____ Push Side: ____ Pull Side: ____ Both Sides: ____

Sweep:
Pro Series Neoprene Bottom Sweep Gasket with SS Retainer: _____
CS Series Neoprene Bottom Sweep Gasket with Aluminum Retainer:____

Threshold:
Pro Series 14-ga Stainless Steel Threshold: ____ HDPE Threshold: ____
CS Series Aluminum Threshold: ____ CS Series Thermally Broken Aluminum Threshold: ___

Additional Hardware:
SS Center Astragal: ____ Pro Series EPDM Seal Astragal with SS Retainer: ____
SS Removable Center Mullion: ____ SS Drip Cap: ____ Wall Stop: ____ Floor Stop: ____
SS Top & Bottom Surface Bolts:____ Floor Stop w/ Hold Open:____

Other: _____ **USDA Compliant:** ☑Yes

WEILAND

WEILAND FIBERGLASS PERSONNEL DOUBLE DOOR

Customer:

Project Name:

Ship to:



THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF WEILAND INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF WEILAND INC IS PROHIBITED

SHOP DRAWINGS NOT APPROVED IN 45 DAYS ARE SUBJECT TO REPRICING & SURCHARGES



ROUGH OPENING
W.I.C. + 4 1/2"
H.I.C. + 2 1/4"



ROUGH OPENING
W.I.C. + 1"
H.I.C. + 1/2"



ROUGH OPENING
W.I.C. + 4 1/2"
H.I.C. + 2 1/4"